

# MXC-2300 Series

## Intel® Atom™ Quad-Core Processor-based Fanless Expandable Embedded Computer with PCI/PCIe Slots

### Features

- Intel® Atom™ E3845 processor with 4 core @1.91 GHz SoC
- 2x DDR3L SO-DIMM, supporting up to 8 GB memory
- 2 PCI + 1 PCIe x4 or 3 PCI expansion slots
- Built-in dual-port isolated CAN and 16-CH isolated DI and DO
- 1 DisplayPort + 1 DVI-I



### Specifications

Model Name	MXC-2300CD-3E1	MXC-2300CD-3S	MXC-2300-3E1	MXC-2300-3S
<b>System Core</b>				
Processor	Intel® Atom™ Processor E3845 Processor, 1.91 GHz, 4 cores; 542/792 MHz graphics frequency (Base/Turbo)			
Chipset	Intel SoC (System on Chip)			
Video	DisplayPort: resolution up to 2560x1600 VGA: resolution up to 2560x1600 DVI: resolution up to 1920x1200			
Memory	4GB DDR3L 1333 MHz SODIMM module, (up to 8 GB with 2 SODIMM sockets)			
<b>I/O Interface</b>				
Expansion slots	2 PCI+1 PCIe x4	3 PCI	2 PCI+1 PCIe x4	3 PCI
Ethernet	2 Intel® GbE ports (Intel® Springville WG1210IT chipset) Teaming function, Wake On LAN			
Serial Ports	2 software-programmable RS-232/422/485 (COM 1&2) with auto-flow control, 2 RS-232 (COM 3&4)			
USB	5 external USB ports (4 USB 2.0 + 1 USB 3.0) + 1 internal USB 2.0			
CAN	2 DB9 isolated CAN port with SJA1000 CAN controller			-
DIO	16-CH DI and 16-CH DO with 1.5KV isolation			-
Mini PCIe	1 internal mini PCIe card socket			-
USIM	1 USIM socket for 3G communication			-
Audio	1 MIC-in and 1 Line-out			
<b>Manageability</b>				
WDT	Hierarchical WDT supported			
SEMA	SEMA 2.2 (Smart Embedded Management Agent)			
<b>Power Supply</b>				
DC Input	Built-in 9-32 V <sub>DC</sub> wide-range DC input pluggable connectors with latch (GND, V-, V+), 2-pin remote power on/off switch			
AC Input	Optional 100 W external AC-DC adapter for AC input			
<b>Storage Device</b>				
SATA HDD	1x onboard SATA-II port for 2.5" HDD/SSD installation			
CompactFlash	1 Type II CF socket CompactFlash socket			
<b>Mechanical</b>				
Optional Fan Module	Optional fan module for heat dissipation, smart fan control			
Dimensions	142 (W) x219 (D) x210(H) mm (WxDxH) (5.84" x 8.76" x 8.4)			
Weight	3.5 kg (7.73 lbs)			
Mounting	Wall-mount kit			
<b>Environmental</b>				
Operating Temperature	Standard: 0°C to 50°C (32° F to 122° F) Extended temperature option*: -20°C to 70°C (-4° F to 158° F) (w/industrial SSD or CF)			
Storage Temperature	-40°C to 85°C (-40° F to 185° F) (excl. HDD/SDD/CF)			
Humidity	~95% @ 40°C (104° F) (non-condensing)			
Vibration	Operating, 5 Grms, 5-500 Hz, 3 axes (w/ CF or SSD) Operating, 0.5 Grms, 5-500 Hz, 3 axes (w/ HDD)			
ESD	Contact +/-4 KV and Air +/-8 KV			
Shock	Operating, 50 G, half sine 11 ms duration (w/ CF or SSD)			
EMC	CE and FCC Class A			
Safety	UL/cUL, CB			

# MXC-2300 Series

## Ordering Information

Model Name	Description	Memory	Expansion Slots	Mini PCIe	CAN	DIO
MXC-2300CD-3E1	Intel® Atom™ E3845 Fanless computer	4 GB DDR3L	2 PCI+1 PCIe x4	1	2	16-CH
MXC-2300CD-3S	Intel® Atom™ E3845 Fanless computer	4 GB DDR3L	3 PCI	1	2	16-CH
MXC-2300-3E1	Intel® Atom™ E3845 Fanless computer	4 GB DDR3L	2 PCI+1 PCIe x4	-	-	-
MXC-2300-3S	Intel® Atom™ E3845 Fanless computer	4 GB DDR3L	3 PCI	-	-	-

## Optional Accessories

MXC-2300 Optional Fan Module	Fan module for MXC-2300 series
500 GB HDD Option	Factory-installed 500 GB SATA hard disk drive (0 °C to 50 °C, 32 °F to 122 °F)
32/64 GB SSD Option	Factory-installed 32/64 GB MLC SATA solid-state drive (0 °C to 70 °C, 32 °F to 158 °F)
32G CF	Factory-installed 32 GB industrial Compact Flash (-40 °C to 85 °C, -40 °F to 185 °F)
100 W AC-DC Adapter	100 W industrial grade A C-DC adapter (-20 °C to 70 °C, -4 °F to 158 °F)
90 W AC-DC Adapter	90 W commercial grade AC-DC adapter (0 °C to 50 °C, 32 °F to 122 °F)
Extended Temperature Option*	Optional screening service to extend the operating temperature to -20 °C to 70 °C (-4 °F to 158 °F)